



# STANDBY GENERATORS

## 35KW<sup>1</sup> COMMERCIAL GENERATOR MODEL OPTIONS

Model	Power (KW)	Alternator	L-N	L-L	Config	# Leads	Phase	Power Factor	Hz	LP Vapor		Natural Gas		Breaker	Controller
										kW	Amps	kW	Amps		
076140	35	35-BSPP-0	120	240	-	4	1	1.0	60	35	146	31.5	131	175	Briggs & Stratton Standard
076141	35	35-TBSPP-0	120	208	WYE	12	3	0.8	60	35	121	31.5	109	150	InteliNano
076142	35	35-TBSPP-0	139	240	WYE	12	3	0.8	60	35	105	31.5	95	125	InteliNano
076143	35	35-TBSPP-0	120	240	Delta	12	3	0.8	60	35	105	31.5	95	125	InteliNano
076144	35	35-TBSPP-0	240	416	WYE	12	3	0.8	60	35	61	31.5	55	70	InteliNano
076145	35	35-TBSPP-0	227	480	WYE	12	3	0.8	60	35	53	31.5	47	60	InteliNano
076340	35	35-BSPP-0	120	240	-	4	1	1.0	60	35	146	31.5	131	175	InteliLite
076341	35	35-TBSPP-0	120	208	WYE	12	3	0.8	60	35	121	31.5	109	150	InteliLite
076342	35	35-TBSPP-0	139	240	WYE	12	3	0.8	60	35	105	31.5	95	125	InteliLite
076343	35	35-TBSPP-0	120	240	Delta	12	3	0.8	60	35	105	31.5	95	125	InteliLite
076344	35	35-TBSPP-0	240	416	WYE	12	3	0.8	60	35	61	31.5	55	70	InteliLite
076345	35	35-TBSPP-0	227	480	WYE	12	3	0.8	60	35	53	31.5	47	60	InteliLite

Not for Prime Power or use where standby systems are legally required, for serious life safety or health hazards, or where lack of power hampers rescue or fire-fighting operation.

<sup>1</sup>This generator is rated in accordance with UL (Underwriters Laboratories) 2200 (stationary engine generator assemblies) and CSA (Canadian Standards Association) standard C22.2 No. 100-04 (motors and generators).